FLOOR SLIP RESISTANCE TESTING CERTIFICATE FLOOR SLIP

Testing Certificate Ref No:

AW/FS/2009010



Client Location Date Tested

Pendulum Equipment Used

Pendulum Serial No Pendulum Calibrated

Slider Type Used (Delete as Required)

Slider Ser No(s) - Batch

Slider Date Expiry

Granite Setts UK ++Samples++ 01 October 2020 KSS Pendulum ST13

20th November 2019

96 slider 96#72

15th December 2020

The Pendulum was used in accordance with the United Kingdom Slip Resistance Group (UKSRG) guidelines for testing floors to ascertain the slip resistance to BS EN 14231. The tests were carried out under: -

- Wet Conditions (Using potable water to cover the whole test area and refreshed between tests).

Dry & sunny conditions

Eight measurements were taken at each condition and in three different horizontal planes (0, 45 and 90 degrees) at each position. The first three measurements were discarded to allow checks for slider stabilisation. The median (average) of the remaining results were then calculated, as advocated by the UKSRG/Health & Safety Executive (HSE). The results for the floors tested are indicated in the table below:

The HSE / UKRSG has determined a minimum Pendulum Test Value reading of 36 must be obtained in all conditions (Dry, Wet, or Contaminated) and on a level surface for a floor to pass the test

Ref	Area/Room	Surface	Ambient Temp (deg C)	Mean (Average) Reading	Pass / Fail
1	Sample	Granite	18c	DRY 62	
		Sawn		WET 42	PASS
				R Rating	11
2	Sample	Granite	18c	DRY 76	
		Finished .		WET 53	PASS
				R Rating	12

Signed on behalf of FloorSlip Ltd:

A.I. Wylie

Name:

: Andrew Wylie

Date:

01/10/20

Valid Until Date: N/A

This test certificate is not valid or original if the embossed company stamp is not present

FloorSlip Ltd -. www.floorslip.co.uk e:mail - info@floorslip.co.uk Tel: 08719 152535 / 08713 155789

Registered Office - The Meridien, 4 Copthall House, Coventry, CV1 2FL Company number: 07757686 Please do NOT reply to this address as it is an unmonitored Address

